



المتحدة للصناعات التعدينية
United Mining Industries

MATERIAL SAFETY DATA SHEET

PRODUCTION NAME : Gypsum Plaster

PRODUCT STANDARD :

It is manufactured according to SASO (ASTM C59/ C59M – 00) specification and Compatible with European specification EN 13279-1 and Gulf specification NO. 2025/1995

USING OF PLASTER GYPSUM :

It is use in internal building as single Coat for wall and ceilings where normal humidity and can be applied by hand.

IDENTIFICATION OF THE PREPARATION AND COMPANY :

COMPANY NAME : United mining industry Company

ADDRESS : Light Industrial Area, Al Razi ST, Yanbu Al Sinaiyah K. S. A

TELEPHONE NO : 0096643968777

FAX NO : 009663962666

COMPOSITION :

Gypsum Plaster are inorganic mineral consist of calcium sulphet ($\text{Ca So}_4 \cdot \frac{1}{2} \text{H}_2\text{O}$) they are made from natural gypsum (Gypsum Rock) using suitable calcination processes .

HAZARDS IDENTIFICATION:

This preparation is not classified as hazardous under European rules.

FIRST AID MEASURES:

Gypsum is a powder consists mainly from calcium sulphet this material is a neutral and Having no health hazards. Just in case you got contaminated by this powder. Just all what you need is to wash the exposed parts by plan water. If this material got To be ingested, it needs to gurgle your nose or moth by water.



Plant Management
Yanbu, P.O. Box: 31491,
T. +966 4 396 8777,
F. +966 4 396 2666,
E-mail: yanbusales@ugc.com.sa

Sales & Marketing Managment:
Jeddah,
T. +966 2 691 3497,
F. +966 2 682 3651,
E-mail: jeddahsales@ugc.com.sa

إدارة المصنع:
بنينج، ص.ب. ٣١٤٩١،
هاتف: ٨٧٧٧ ٣٩٦ ٤٩٦٦
فاكس: ٢٦٦٦ ٣٩٦ ٤٩٦٦
yanbusales@ugc.com.sa

إدارة المبيعات و التسويق:
جدة،
هاتف: ٣٤٩٧ ٢ ٦٩١ ٩٦٦
فاكس: ٣٦٦ ٢ ٦٨٢ ٩٦٦
jeddahsales@ugc.com.sa

